

RM2 - RM

FORESTRY GRABS - GRAPPINS A BOIS - HOLZGREIFER - PINZAS CARGAS-TRONCOS



Abbinamenti consigliati per escavatori

Suggested combinations for excavators - *Couplages conseillées pour pelles*
Empfohlene Kupplungen für Bagger - *Combinaciones recomendadas para las excavadoras*

ton	RM2 1650	RM2 1650 HD	RM2 1650 FX	RM 1800	RM 1800 HD	RM 1800 FX	RM 2000	RM 2000 HD
8,0 - 10,0	RM2 1650							
10,0 - 11,0	RM2 1650 HD							
11,0 - 12,0	RM2 1650 HD							
9,0 - 10,5	RM2 1650 FX							
10,0 - 11,0	RM 1800							
11,0 - 12,0	RM 1800							
12,0 - 16,0	RM 1800 HD							
11,0 - 12,0	RM 1800 FX							
10,0 - 11,0	RM 2000							
11,0 - 12,0	RM 2000							
13,0 - 16,0	RM 2000 HD							

A

CR 5
CR 5
CR 6
CR 5
CR 6
CR 6
CR 5
CR 6
CR 6

B

KAR 02
KAR 02
KAR 03
KAR 02
KAR 03
KAR 06
KAR 02
KAR 03
KAR 03

A Attacco singolo perno
One pin connection
Attelage à axe simple
Verbindung mittels Einfachbolzen
Conexión de perno simple

B Kit per adattatore attacco rapido
Kit for quick connection adaptor
Kit pour adaptateur attelage rapide
Kit für Schnellwechsler-Adapterplatte
Kit para adaptador de conexión rápida

Rotatori consigliati
Recommended rotators
Rotateurs recommandés
Empfohlene Drehmotoren
Rotadores recomendados

ton	C 110 F	C 160 F
8,0 - 12,0		
12,0 - 16,0		

PINZE FORESTALI

ton 8,0 - 16,0 kg. 4000 - 7000

		RM2 1650	RM2 1650 HD	RM2 1650 FX	RM 1800	RM 1800 HD	RM 1800 FX	RM 2000	RM 2000 HD
ton		8,0 - 10,0	10,0 - 12,0	9,0 - 10,5	10,0 - 12,0	12,0 - 16,0	11,0 - 14,0	10,0 - 12,0	13,0 - 16,0
Kg.		4000	4500	3000	5500	7000	5000	5500	7000
Kg.		263	295	320	400	440	440	450	505
mm		1650	1650	1650	1820	1820	1820	2010	2010
bar		230	300	250	250	250	480	250	250
lt.		65	65	65	90	90	90	90	90
m ²		0.31	0.31	0.34	0.40	0.40	0.40	0.48	0.48
mm		935	935	960	1005	1005	1135	1100	1100
mm		100	100	100	120	120	120	150	150
mm		1030	1030	1010	1180	1180	1180	1225	1225
mm		600	600	650	680	680	810	730	730
mm		550	550	535	590	590	590	620	620
mm		905	905	920	980	980	1110	1010	1010
mm		468	498	575	580	630	630	580	630

* Resistenza strutturale a sollevamento - Résistance structurelle au levage - Structural strength to lifting - Strukturelle Festigkeit zu heben - Resistencia estructural a la elevación


Altri abbinamenti consigliati

Other suggested combinations - *Couplages divers conseillées*
Weitere empfohlene Kupplungen - *Otras combinaciones recomendadas*

kg.	RM2 1650	C 65 F	KIT 1/2"
4000	RM2 1650	C 65 F	KIT 1/2"
4500	RM2 1650 HD	C 110 F	KIT 1/2"
5500	RM 1800	C 110 F	KIT 1/2"
5500	RM 1800	C 160 F	KIT 1/2"
7000	RM 1800 HD	C 160 F	KIT 1/2"
5500	RM 2000	C 110 F	KIT 1/2"
5500	RM 2000	C 160 F	KIT 1/2"
7000	RM 2000 HD	C 160 F	KIT 1/2"

RM2 - RM

FORESTRY GRABS - GRAPPINS A BOIS - HOLZGREIFER - PINZAS CARGAS-TRONCOS



RM
Perni conici registrabili
Tapered sleeve-pins
Axes à fixation conique enregistrable
Einstellbare konische Bolzen
Pernos cónicos ajustables



PINZE FORESTALI

ton 8,0 - 15,0 kg. 4000 - 6000

		RM2 1650 SP	RM2 1650 XT	RM 1800 HP	RM 2000 HP
	ton	8,0 - 11,00	10,0 - 12,00	12,0 - 15,00	12,0 - 15,00
	Kg.	4000	4500	6000	6000
	Kg.	300	305	440	495
	mm	1650	1650	1845	2020
	bar	230	250	250	250
	lt.	65	65	90	90
	m ²	0.30	0.31	0.39	0.47
	mm	980	980	985	1060
	mm	100	100	120	150
	mm	1030	1030	1180	1225
	mm	590	600	680	730
	mm	550	550	570	590
	mm	900	905	960	980
	mm	530	530	640	640

* Resistenza strutturale a sollevamento - Résistance structurelle au levage - Structural strength to lifting - Strukturelle Festigkeit zu heben - Resistencia estructural a la elevación

Abbinamenti consigliati per escavatori

Suggested combinations for excavators - *Couplages conseillées pour pelles*
Empfohlene Kupplungen für Bagger - *Combinaciones recomendadas para las excavadoras*

	A	B
ton	CR 5	KAR 02
8,0 - 9,0	CR 5	KAR 02
9,0 - 11,0	CR 5	KAR 02
10,0 - 12,0	CR 5	KAR 02
11,0 - 12,0	CR 5	KAR 02
12,0 - 16,0	CR 6	KAR 03
12,0 - 16,0	CR 6	KAR 03

A Attacco singolo perno
One pin connection
Attelage à axe simple
Verbindung mittels Einfachbolzen
Conexión de perno simple

B Kit per adattatore attacco rapido
Kit for quick connection adaptor
Kit pour adaptateur attelage rapide
Kit für Schnellwechsler-Adapterplatte
Kit para adaptador de conexión rápida

Rotatori consigliati
Recommended rotators
Rotateurs recommandés
Empfohlene Drehmotoren
Rotadores recomendados

ton	kg.
8,0	C 65 F
9,0 - 11,0	C 110 F
11,0 - 16,0	C 160 F

Altri abbinamenti consigliati

Other suggested combinations - *Couplages divers conseillées*
Weitere empfohlene Kupplungen - *Otras combinaciones recomendadas*

kg.			
4000	RM2 1650 HP	C 65 F	KIT 1/2"
4000	RM2 1650 HP	C 110 F	KIT 1/2"
4500	RM2 1650 XT	C 110 F	KIT 1/2"
6000	RM 1800 HP	C 110 F	KIT 1/2"
6000	RM 1800 HP	C 160 F	KIT 1/2"
6000	RM 2000 HP	C 160 F	KIT 1/2"